

CONFIDENTIAL

STATE OF SOUTH DAKOTA
PUBLIC UTILITIES COMMISSION

IN THE MATTER OF THE PETITION OF
MCCOOK COOPERATIVE TELEPHONE
COMPANY FOR ARBITRATION
PURSUANT TO THE
TELECOMMUNICATIONS ACT OF 1996
TO RESOLVE ISSUES RELATED TO
THE INTERCONNECTION
AGREEMENT WITH ALLTEL, INC.

Docket No. TC07-112

DIRECT TESTIMONY


OF

NATHAN A. WEBER

**DIRECT TESTIMONY OF NATHAN WEBER
ON BEHALF OF
MCCOOK COOPERATIVE TELEPHONE COMPANY**

1 **Q1. Please state your name, employer, business address and telephone number.**
2
3 A1. My name is Nathan Weber. I am the Director of Engineering of Vantage Point
4 Solutions, Inc. ("Vantage Point"). My business address is 2211 North Minnesota
5 Street, Mitchell, South Dakota, 57301.

6 **Q2. On whose behalf are you testifying?**
7
8 A2. I am testifying on behalf of McCook Cooperative Telephone Company
9 ("McCook"). Based on my experience working with McCook for over 5 years, I
10 know that McCook provides local telephone exchange service and exchange
11 access services in South Dakota and is engaged in the provision of general
12 telecommunications services in the State of South Dakota subject to the
13 jurisdiction of the South Dakota Public Utilities Commission ("Commission").



CONFIDENTIAL

1 **Q3. Generally, what types of services does Vantage Point perform?**

2
3 A3. Vantage Point is a telecommunications engineering and consulting company
4 whose services include long range communication plans and feasibility studies,
5 emerging technology analysis and migration studies, telecommunications
6 electronic equipment engineering, outside plant engineering, field services
7 engineering and regulatory consulting.

8 **Q4. What are your duties and responsibilities at Vantage Point?**

9
10 A4. I am responsible for providing consulting and engineering services to clients in a
11 wide array of technical and regulatory areas associated with telecommunications.
12 Our client base consists of small Independent Telephone Companies such as
13 McCook. Vantage Point has more than 80 fulltime employees on staff. I am also
14 responsible for the normal duties you would expect from the director of
15 engineering for a company of our size.

16 **Q5. What is your educational background?**

17
18 A5. I have a Bachelor of Science in Electrical Engineering from South Dakota State
19 University in Brookings, South Dakota.

20 **Q6. Do you hold any professional engineering licenses?**

21 A6. Yes. I am a licensed professional engineer in North Dakota and South Dakota. I
22 am also a member of the National Council of Examiners for Engineering and
23 Surveying (NCEES).

24 **Q7. Do you have a resume of your experience?**

25 A7. Yes, it is attached to my testimony as Exhibit NW-D-1.

26

1 **Q8. What is the purpose of your direct testimony?**

2

3 A8. The purpose of my direct testimony is to provide technical facts relating to the
4 Arbitration¹ between McCook and Alltel Communications, Inc. (Alltel). I will
5 provide information relating to Issue 1 identified in the Petition for Arbitration for
6 McCook (referred to herein as the "Petition"). This issue was presented in the
7 Petitions as follows: "Is the reciprocal compensation rate for IntraMTA Traffic
8 proposed by Telco appropriate pursuant to 47 U.S.C. § 252(d)(2)?" Specifically, I
9 will explain the engineering inputs and how they comply with FCC rule
10 51.505(b)(1).

11 **Q9. Can you provide a general overview of the engineering inputs provided for**
12 **the Forward-Looking Economic Cost (FLEC) model?**

13

14 A9. The engineering inputs associated with the McCook FLEC model consist of
15 several components. First, the "Switching" network includes items associated
16 with the deployment of a typical Class 4/5 voice switch. The individual
17 components that were included in the FLEC engineering design for the switching
18 network are separated into four main categories including Common, Line Cards,
19 Line Interface Cards, and Trunk Cards. The "Inter-Exchange Transport" cost
20 estimates associated with the McCook FLEC study included Inter-Exchange
21 Transport electronics and Outside Plant (OSP) cable to interconnect the respective
22 exchanges. The Inter-Exchange Transport cost estimates were divided into three
23 main categories including Base Costs, Line Costs, and Tributary Costs. Similarly,

¹ In The Matter of the Petition Of McCook Cooperative Telephone Company for Arbitration Pursuant to the Telecommunications Act Of 1996 To Resolve Issues Related to The Interconnection Agreement With Alltel, Inc. (referred to herein as the "Petition").

CONFIDENTIAL

the OSP cable construction cost estimates were separated into "Town" and "Rural" categories.

Q10. What voice switching technology and architecture was assumed in the development of the FLEC capital investment estimates?

A10. For the purposes of the FLEC engineering model for McCook, it was assumed that they would deploy "Softswitching" technology within their network. The Softswitching technology is a packet, voice switching technology. This type of switch will allow for either Time Division Multiplexing (TDM) interfaces or packet interfaces to be deployed. The Softswitch uses packet technology for switching voice traffic, but this technology allows for either packet or TDM circuit connections to be used for line or trunk interfaces.

The Softswitch architecture, as commonly implemented in the industry and in the McCook FLEC engineering model, consists of four components including the Call Agent, Signaling Gateway, Media Gateway, and Outboard Line Bays (OLB's). The function of a Call Agent is to provide services such as media and signaling gateway control and billing, call routing logic, Communications Assistance for Law Enforcement Act (CALEA) support, and miscellaneous subscriber services such as call waiting, distinctive ringing, and off-premise extensions. The Signaling Gateway's function is to provide the Signaling System 7 (SS7) signaling interface for the Softswitch. In addition, the Media Gateway provides media (voice) switching and processing capabilities. A diagram depicting this architecture is attached to my testimony as Exhibit NW-D-2.

The OLB equipment is used to provide analog plain old telephone service (POTS) line interfaces to the end subscribers. In a legacy digital switching

CONFIDENTIAL

1 architecture, the analog POTS lines were typically equipped in separate
2 equipment bays, and the switch processors communicated with the analog POTS
3 line cards via inter-bay interfaces and cables. One attribute of Softswitching
4 platforms that is unique when compared to legacy digital switching architectures
5 is the absence of on-board analog POTS line cards within the Media Gateway
6 chassis. For Softswitch deployments, it is typically necessary to use devices such
7 as OLB terminals, which are sometimes referred to as Digital Loop Carriers
8 (DLC's), to provide analog POTS line card interfaces to serve the subscribers.
9 For the McCook FLEC engineering design, OLB's were assumed to provide this
10 functionality. Like other Softswitching networks, the OLB's assumed in the
11 McCook FLEC engineering design function as virtual extensions of the Class 5
12 switch.

13 For McCook, the FLEC engineering design assumed the use of a
14 distributed Softswitching network. As part of this architecture, centralized Call
15 Agents are assumed to be deployed at each "host" switching location. The
16 location that is designed to include the Call Agents for McCook is Salem.

17 A single Media Gateway with a Signaling Gateway is included for each
18 exchange. For new switching network deployments, this architecture is
19 commonly deployed by telecommunications service providers whose number of
20 subscribers and scope of services offered are comparable to McCook.

21 The FLEC engineering design for McCook also includes the deployment
22 of "Intermediate Tandem" functionality at the Salem exchange. In this
23 architecture, the trunks from the various McCook exchanges are aggregated in the

CONFIDENTIAL

1 Salem switch. The purpose of this function is to provide improved efficiencies by
2 maximizing the "fill" of the outgoing trunks to the Access Tandem provider. The
3 assumed efficiency of the Intermediate Tandem function reduces the quantity of
4 trunks to the Access Tandem provider by approximately 20 percent.

5 **Q11. Can you explain the design parameters were considered when developing the**
6 **switching network architecture for the FLEC model?**
7

8 A11. The FLEC engineering design for McCook was developed to provide an efficient
9 voice switching network that offers the appropriate grade of service for the
10 subscribers of McCook. The ability to provide voice services with 99.999%
11 availability is paramount to telecommunications service providers such as
12 McCook. One key attribute that is included in the design is emergency stand-
13 alone capabilities for all exchanges. This emergency stand-alone functionality
14 offers the ability for subscribers to make local calls in the event that the
15 communication path to the Call Agent is severed.

16 In addition, the switching network is designed to adhere to the South
17 Dakota service standards for telecommunications companies set forth in the
18 Administrative Rules for South Dakota. Specifically, the switching system was
19 assumed to include custom calling feature such as call waiting, call forwarding,
20 abbreviated dialing, caller identification, and three-way calling as set forth in
21 A.R.S.D. Section 20:10:33:04. Similarly, the switching network is designed to
22 adhere to A.R.S.D. Section 20:10:33:05 which states that during any busy hour,
23 the telecommunications service provider network must allow for a minimum of
24 98 percent of call attempts to receive dial tone within three (3) seconds, a
25 minimum of 98 percent of properly dialed calls for extended service area to be

CONFIDENTIAL

properly terminated, and a minimum of 98 percent of properly dialed calls routed entirely over the network of the local exchange carrier to be properly terminated.

Other required functions included in the FLEC engineering design for the switching network include E-911 service support, as well as CALEA support. In addition, the switching network architecture for the McCook FLEC engineering design included SS7 signaling capabilities.

Q12. In your expert opinion, is the technology and architecture used for the FLEC model considered to be an economical, long-term solution?

A12. Yes. As stated previously, the distributed Softswitching architecture assumed for the McCook FLEC model is a commonly deployed model for new switching network implementations. One primary reason that this architecture is commonly deployed in this market space is due to the fact that it is a robust and cost-effective solution for telecommunications service providers.

Q13. With regards to the engineering design for the "Switching" network for McCook, what components comprise the various categories (e.g. Common, Line Cards, Line Interface Cards, and Trunk Cards) for the FLEC capital investment estimates?

A13. The Switching network investments for McCook are separated into four (4) primary categories including "Common", "Line Cards", "Line Interface Cards", and "Trunk Cards." First, the category of Common items includes components that are common to the system. This category of network investment does not include any voice circuit interface cards that are active in the proposed system. The items included in the "Common" investment category include, but are not limited to, the following: Call Agent hardware, Call Agent software, Media Gateway chassis (including redundant central processing units, power supplies,

CONFIDENTIAL

1 and cooling fans), Media Gateway software, Signaling Gateway hardware, EMS
2 and Web Provisioning systems, feature right-to-use fees (e.g. CALEA, Centrex,
3 Web Provisioning, Emergency Stand-Alone, and concurrent call license),
4 Ethernet interface, OLB chassis, OLB processors, OLB administration interface,
5 and spare circuit cards. A diagram depicting the allocation of the switching
6 network components to the respective categories is attached to my testimony as
7 Exhibit NW-D-3. In addition, a component level pricing breakdown for each
8 category of investment at each respective exchange is attached to my testimony as
9 Exhibit NW-D-4.

10 The "Line Cards" category includes only the analog POTS line cards that
11 are equipped in the OLB chassis. No other equipment is included in this group.

12 Next, the "Line Interface Card" category includes equipment in the Media
13 Gateway and OLB terminals. The items included are the circuit interface cards
14 that provide DS-1 GR-303 connectivity between the Media Gateway and the OLB
15 terminal.

16 Finally, the "Trunk Card" category includes circuit interface cards in the
17 Media Gateway that are used for trunk interfaces. In other words, these circuit
18 cards provide communication from the Media Gateway to the Public Switched
19 Telephone Network (PSTN).

20 A loading factor is included to each investment category for the respective
21 locations to account for miscellaneous items. Specifically, a 10 percent factor is
22 incorporated in each category to account for installation materials and labor. In

CONFIDENTIAL

1 addition, a 15 percent factor is included for miscellaneous costs such as taxes and
2 engineering.

3
4 **Q14. What technology and configuration options were assumed for the Inter-**
5 **Exchange Transport cost estimates?**

6
7 A14. With regards to the FLEC engineering model designed for the McCook intra-
8 company, Inter-Exchange Transport network, it is assumed that the network
9 would be implemented as an OC-192 Synchronous Optical NETworking
10 (SONET) transport network. In accordance with South Dakota Codified Law,
11 Chapter 49-31-60, the transport network architecture was selected to provide
12 highly available, switched, survivable optical transport rings between the
13 respective exchanges. In order to accomplish this, the proposed network is
14 designed in a ring architecture in which diverse fiber paths are utilized. This is a
15 common network design architecture that limits the potential for an individual
16 exchange from being isolated from the rest of the network due to a single fiber
17 optic cable cut. SONET architectures typically offer rapid traffic recovery in the
18 event of a fiber optic cable cut or optical transceiver failure. The target failure
19 recovery time for SONET networks is approximately 50 milliseconds.

20 The proposed SONET infrastructure for McCook is assumed to be a
21 carrier-grade solution that includes redundant power supplies, processor units,
22 switch fabric, timing units, and cooling fans. In addition, the system is designed
23 to offer both Synchronous Transport Signal (STS) and Virtual Tributary (VT)
24 switching capabilities to allow for granular traffic management capabilities. The
25 solution included in the FLEC engineering design is required to support a variety

CONFIDENTIAL

1 of circuit interfaces such as OC-192, OC-48, OC-12, OC-3, DS-3, DS-1, Gigabit
2 Ethernet, and 10/100 BaseT. With the exception of the Ethernet interface cards,
3 the tributary interfaces are configured to provide hardware redundancy to ensure
4 an appropriate level of availability. Traditional hardware redundancy is typically
5 not available for Ethernet interfaces today.

6 **Q15. How were the quantities of circuit interface cards assumed for the FLEC**
7 **capital investment estimates derived?**

8
9 A15. The quantities of circuit interface cards assumed in the FLEC engineering design
10 are based upon the circuit requirements for the transport of the Switching network
11 circuits, as well as miscellaneous special access circuits. The SONET solution
12 assumed for this FLEC engineering design has circuit interface cards that have
13 standard densities for interface port quantities. For example, the quantity of DS-1
14 ports provided on a single DS-1 interface card is 28. Similarly, the DS-3 circuit
15 interface cards include eight DS-3 interfaces and the 10/100 BaseT Ethernet
16 circuit interface cards include four 10/100 BaseT interfaces.

17 With regards to the SDN Terminal at the Salem Hut, it is assumed that the
18 quantity of interfaces equipped at this location will match the equipment
19 configuration that is presently deployed at this location.

20 **Q16. With regards to the engineering design for the “Inter-Exchange Transport”**
21 **network for McCook, what components comprise the various categories (e.g.**
22 **Base Cost, Line Interface, Tributary Interface, etc.) for the FLEC capital**
23 **investment estimates?**

24
25 A16. The “Inter-Exchange Transport” electronics assumed for the FLEC engineering
26 design included items that are divided into three (3) primary categories including
27 “Base Cost”, “Line Interface”, and “Tributary Interface.” For example the items

CONFIDENTIAL

1 included in the "Base Cost" category are essentially the common hardware and
2 software elements that are required for the system. Specifically, these items
3 include the equipment chassis, cooling fan modules, CPU, Digital
4 Communications Channel (DCC) units, alarm interface units, timing and
5 synchronization modules, STS switch fabric, VT1.5 switch fabric, system
6 software, Element Management System software, and miscellaneous cabling. A
7 diagram depicting this categorization of components is attached to my testimony
8 as Exhibit NW-D-5. In addition, a component level pricing breakdown for each
9 category of investment at each respective exchange is attached to my testimony as
10 Exhibit NW-D-6. The "Line Interface" cost category includes the OC-192 circuit
11 interfaces cards that are necessary to provide the optical line interfaces between
12 adjacent SONET network elements.

13 Finally, the "Tributary Interface" costs include a variety of circuit
14 interface cards that are required to add and drop traffic at each respective location.
15 These "Tributary Interface" cards assumed for McCook include OC-48, DS-3,
16 DS-1, Gigabit Ethernet, and 10/100 BaseT Ethernet circuit interface cards.

17 A loading factor is included to each investment category for the respective
18 locations to account for miscellaneous items. Specifically, a 10 percent factor is
19 incorporated in each category to account for installation materials and labor. In
20 addition, a 15 percent factor is included for miscellaneous costs such as taxes and
21 engineering.

CONFIDENTIAL

1 **Q17. What methodology was utilized to determine the total route mile distance for**
2 **Outside Plant (OSP) fiber optic cable construction between the adjacent**
3 **locations?**

4
5 A17. In the development of the FLEC engineering design, it was assumed that the fiber
6 optic transport infrastructure would be implemented to allow for diverse fiber
7 routes to and from each respective exchange. This design methodology complies
8 with South Dakota Codified Law, Chapter 49-31-60, by enabling switched
9 survivable rings. In addition, diverse fiber optic cable routing is commonly
10 implemented by companies such as McCook to prevent a single fiber optic cable
11 cut from isolating an exchange from the rest of the network. The design of the
12 fiber optic cable route assumed cable placement that provides for the most
13 probable and efficient route between adjacent exchanges. It is assumed that
14 public right-of-way will be used for this fiber optic cable construction. Therefore,
15 the assumed cable route was designed to follow existing roads. The approximate
16 distance for the "Town" and "Rural" construction were summed to provide the
17 total route mile distance between the respective exchanges. A diagram depicting
18 the general fiber optic cable route is attached to my testimony as Exhibit
19 NW-D-7.

20 **Q18. What is considered "Town" construction versus "Rural" construction?**
21

22 A18. For the purposes of this design, it was assumed that the fiber optic cable would be
23 constructed to the existing central office building in each exchange. Any cable
24 routes that fall within the city limits of a community, or within an area that has a
25 population density consistent with a town environment, were designated as
26 "Town" construction. The routes that fall outside the city limits (or comparable

CONFIDENTIAL

1 population density) are deemed to be "Rural" construction. A diagram depicting
2 the separation of town and rural construction, as well as the general components
3 included in each category, is attached to my testimony as Exhibit NW-D-8.

4 **Q19. How was the per-foot rate for the OSP "Town" construction estimates**
5 **determined?**

6
7 A19. The OSP "Town" construction per-foot costs were developed by analyzing
8 deployment costs for actual "Town" construction for communities in South
9 Dakota. The costs used to develop the per-foot rate were based upon actual OSP
10 costs for Fiber to the Premises (FTTP) projects in four communities. The
11 communities whose FTTP construction pricing data was utilized include Brandon,
12 Garretson, Site C (South Dakota Company that is not part of this litigation), and
13 Mitchell.

14 The unit tabulations from the construction for these communities were
15 reviewed, and any units associated with a subscriber drop (connection to a
16 subscriber location) were removed from the calculation. This was done so that
17 only "main-line" cable construction was included in the estimates. The subscriber
18 drop construction costs were removed from the per-foot calculation due to the fact
19 that it is not representative of the OSP town construction required for Inter-
20 Exchange transport.

21 The total footage for the four communities was summed, along with the
22 total construction cost for the fiber optic cable construction in these communities.
23 The sum of the total construction in these four communities is 1,525,730 feet of
24 construction at a price of \$18,203,871.57. The resulting total cost was divided by
25 the total footage to determine the average cost per foot. The outcome was a total

CONFIDENTIAL

1 cost per foot estimate of \$11.93. A loading factor of 15% for engineering and
2 taxes was added to determine the final result of \$13.72 per foot for OSP town
3 construction. A detailed pricing breakdown showing the unit quantities and unit
4 costs used to derive the per-foot pricing estimate for town construction is attached
5 to my testimony as Exhibit NW-D-9.

6 **Q20. How was the per-mile rate for the OSP "Rural" construction estimates**
7 **determined?**

8
9 A20. The OSP Rural construction estimates for McCook were based upon actual rural
10 fiber optic cable construction costs for Santel Cooperative Communications
11 (Santel). The terrain for McCook and Santel are comparable, and both companies
12 can expect virtually equivalent costs for constructing fiber optic cable in rural
13 portions of their exchanges. The pricing of \$592,666.64 is the construction cost
14 for a 74.22 mile OSP project that was bid for Santel in March 2003. An annual
15 "normalization" factor of 5% was added to the OSP bid price to determine the
16 estimated current pricing for rural construction. The result of this normalization
17 is an estimated cost for construction of \$720,390.01 for an equivalent project
18 being bid in December 2007. Dividing this normalized total by 74.22 routes
19 miles provides an average cost per mile of approximately \$9,705 in the McCook
20 service territories. This result was subsequently multiplied by a 15% loading
21 factor to account for items such as engineering and taxes. The final, loaded cost
22 per mile for rural OSP construction is estimated at approximately \$11,161. A
23 detailed pricing breakdown showing the unit quantities and unit costs used to
24 derive the per-foot pricing estimate for town construction is attached to my
25 testimony as Exhibit NW-D-10.

CONFIDENTIAL

1 **Q21. Does that conclude your testimony?**

2 A21. Yes. However, I wish to reserve the opportunity to supplement this testimony in
3 the future, if necessary.