

---

**BEFORE THE PUBLIC UTILITIES COMMISSION  
OF THE STATE OF SOUTH DAKOTA**

---

**IN THE MATTER OF THE APPLICATION  
OF NAVIGATOR HEARTLAND  
GREENWAY, LLC FOR A PERMIT UNDER  
THE SOUTH DAKOTA ENERGY  
CONVERSION AND TRANSMISSION  
FACILITIES ACT TO CONSTRUCT THE  
HEARTLAND GREENWAY PIPELINE IN  
SOUTH DAKOTA**

**HP22-002**

**RICHARD KUPREWICZ  
INITIAL PRE-FILED TESTIMONY  
IN SUPPORT OF  
LANDOWNER INTERVENORS**

---

**Q: Please state your name and purpose for providing testimony in these proceedings.**

A: My name is Richard Kuprewicz. The purpose of my testimony is to provide the PUC information helpful when considering the threat of serious injury to the environment, to the social condition, and substantial impairment to the health, safety or welfare of current and expected inhabitants should the PUC approve this Application. In addition, when there is negative impact on or threats to the foregoing considerations that also leads to negative economic impacts.

**Q: What experience, education, training, or background qualify you to provide opinions and your concerns as you have herein?**

A: Please see a summary of my education and experience in **Attachment No. 1**.

**Q: Does Attachment No. 2 to this testimony describe your opinions and concerns that you want the PUC to be aware of relative to the proposed CO2 pipeline in question?**

A: Yes, that is a true and accurate copy of an article I authored for the Pipeline Safety Trust on this subject. I stand by my positions and opinions discussed therein and am competent to testify about them as necessary. I urge the PUC to carefully consider this testimony during the Hearing in this matter and in your deliberations. I further

reserve the right to amend or modify these opinions upon presentation of any additional information that may justify such a change.

/s/ Richard Kuprewicz

Richard Kuprewicz

# Attachment No. 1

## Curriculum Vitae.

**Richard B. Kuprewicz**

8151 164<sup>th</sup> Ave NE  
Redmond, WA 98052

Tel: 425-802-1200 (Office)

E-mail: kuprewicz@comcast.net

---

**Profile:**

As president of Accufacts Inc., I specialize in gas and liquid pipeline investigation, auditing, risk management, siting, construction, design, operation, maintenance, training, SCADA, leak detection, management review, emergency response, and regulatory development and compliance. I have consulted for various local, state and federal agencies, NGOs, the public, and pipeline industry members on pipeline regulation, operation and design, with particular emphasis on operation in unusually sensitive areas of high population density or environmental sensitivity.

---

**Employment:**

**Accufacts Inc.**

**1999 – Present**

Pipeline regulatory advisor, incident investigator, and expert witness on all matters related to gas and liquid pipeline siting, design, operation, maintenance, risk analysis, and management.

**Position:** President  
**Duties:** > Full business responsibility  
> Technical Expert

**Alaska Anvil Inc.**

**1993 – 1999**

Engineering, procurement, and construction (EPC) oversight for various clients on oil production facilities, refining, and transportation pipeline design/operations in Alaska.

**Position:** Process Team Leader  
**Duties:** > Led process engineers group  
> Review process designs  
> Perform hazard analysis  
> HAZOP Team leader  
> Assure regulatory compliance in pipeline and process safety management

**ARCO Transportation Alaska, Inc.**

**1991 - 1993**

Oversight of Trans Alaska Pipeline System (TAPS) and other Alaska pipeline assets for Arco after the Exxon Valdez event.

**Position:** Senior Technical Advisor  
**Duties:** > Access to all Alaska operations with partial Arco ownership  
> Review, analysis of major Alaska pipeline projects

**ARCO Transportation Co.**

**1989 – 1991**

Responsible for strategic planning, design, government interface, and construction of new gas pipeline projects, as well as gas pipeline acquisition/conversions.

**Position:** Manager Gas Pipeline Projects  
**Duties:** > Project management  
> Oil pipeline conversion to gas transmission  
> New distribution pipeline installation  
> Full turnkey responsibility for new gas transmission pipeline, including FERC filing

**Four Corners Pipeline Co.**

**1985 – 1989**

Managed operations of crude oil and product pipelines/terminals/berths/tank farms operating in western U.S., including regulatory compliance, emergency and spill response, and telecommunications and SCADA organizations supporting operations.

- Position:** Vice President and Manager of Operations  
**Duties:**
- > Full operational responsibility
  - > Major ship berth operations
  - > New acquisitions
  - > Several thousand miles of common carrier and private pipelines

**Arco Product CQC Kiln**

**1985**

Operations manager of new plant acquisition, including major cogeneration power generation, with full profit center responsibility.

- Position:** Plant Manager  
**Duties:**
- > Team building of new facility that had been failing
  - > Plant design modifications and troubleshooting
  - > Setting expense and capital budgets, including key gas supply negotiations
  - > Modification of steam plant, power generation, and environmental controls

**Arco Products Co.**

**1981 - 1985**

Operated Refined Product Blending, Storage and Handling Tank Farms, as well as Utility and Waste Water Treatment Operations for the third largest refinery on the west coast.

- Position:** Operations Manager of Process Services  
**Duties:**
- > Modernize refinery utilities and storage/blending operations
  - > Develop hydrocarbon product blends, including RFGs
  - > Modification of steam plants, power generation, and environmental controls
  - > Coordinate new major cogeneration installation, 400 MW plus

**Arco Products Co.**

**1977 - 1981**

Coordinated short and long-range operational and capital planning, and major expansion for two west coast refineries.

- Position:** Manager of Refinery Planning and Evaluation  
**Duties:**
- > Establish monthly refinery volumetric plans
  - > Develop 5-year refinery long range plans
  - > Perform economic analysis for refinery enhancements
  - > Issue authorization for capital/expense major expenditures

**Arco Products Co.**

**1973 - 1977**

Operating Supervisor and Process Engineer for various major refinery complexes.

- Position:** Operations Supervisor/Process Engineer  
**Duties:**
- > FCC Complex Supervisor
  - > Hydrocracker Complex Supervisor
  - > Process engineer throughout major integrated refinery improving process yield and energy efficiency

---

**Qualifications:**

Served for over fifteen years as a member representing the public on the federal Technical Hazardous Liquid Pipeline Safety Standards Committee (THLPSSC), a technical committee established by Congress to advise PHMSA on pipeline safety regulations.

Committee members are appointed by the Secretary of Transportation.

Served seven years, including position as its chairman, on the Washington State Citizens Committee on Pipeline Safety (CCOPS).

Positions are appointed by the governor of the state to advise federal, state, and local governments on regulatory matters related to pipeline safety, routing, construction, operation and maintenance.

Served on Executive subcommittee advising Congress and PHMSA on a report that culminated in new federal rules concerning Distribution Integrity Management Program (DIMP) gas distribution pipeline safety regulations.

As a representative of the public, advised the Office of Pipeline Safety on proposed new liquid and gas transmission pipeline integrity management rulemaking following the pipeline tragedies in Bellingham, Washington (1999) and Carlsbad, New Mexico (2000).

Member of Control Room Management committee assisting PHMSA on development of pipeline safety Control Room Management (CRM) regulations.

Certified and experienced HAZOP Team Leader associated with process safety management and application.

**Education:**

MBA (1976)  
BS Chemical Engineering (1973)  
BS Chemistry (1973)

Pepperdine University, Los Angeles, CA  
University of California, Davis, CA  
University of California, Davis, CA

---

### **Publications in the Public Domain:**

1. "An Assessment of First Responder Readiness for Pipeline Emergencies in the State of Washington," prepared for the Office of the State Fire Marshall, by Hanson Engineers Inc., Elway Research Inc., and Accufacts Inc., and dated June 26, 2001.
2. "Preventing Pipeline Failures," prepared for the State of Washington Joint Legislative Audit and Review Committee ("JLARC"), by Richard B. Kuprewicz, President of Accufacts Inc., dated December 30, 2002.
3. "Pipelines - National Security and the Public's Right-to-Know," prepared for the Washington City and County Pipeline Safety Consortium, by Richard B. Kuprewicz, dated May 14, 2003.
4. "Preventing Pipeline Releases," prepared for the Washington City and County Pipeline Safety Consortium, by Richard B. Kuprewicz, dated July 22, 2003.
5. "Pipeline Integrity and Direct Assessment, A Layman's Perspective," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated November 18, 2004.
6. "Public Safety and FERC's LNG Spin, What Citizens Aren't Being Told," jointly authored by Richard B. Kuprewicz, President of Accufacts Inc., Clifford A. Goudey, Outreach Coordinator MIT Sea Grant College Program, and Carl M. Weimer, Executive Director Pipeline Safety Trust, dated May 14, 2005.
7. "A Simple Perspective on Excess Flow Valve Effectiveness in Gas Distribution System Service Lines," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated July 18, 2005.
8. "Observations on the Application of Smart Pigging on Transmission Pipelines," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated September 5, 2005.
9. "The Proposed Corrib Onshore System - An Independent Analysis," prepared for the Centre for Public Inquiry by Richard B. Kuprewicz, dated October 24, 2005.
10. "Observations on Sakhalin II Transmission Pipelines," prepared for The Wild Salmon Center by Richard B. Kuprewicz, dated February 24, 2006.
11. "Increasing MAOP on U.S. Gas Transmission Pipelines," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated March 31, 2006. This paper was also published in the June 26 and July 1, 2006 issues of the Oil & Gas Journal and in the December 2006 issue of the UK Global Pipeline Monthly magazines.
12. "An Independent Analysis of the Proposed Brunswick Pipeline Routes in Saint John, New Brunswick," prepared for the Friends of Rockwood Park, by Richard B. Kuprewicz, dated September 16, 2006.
13. "Commentary on the Risk Analysis for the Proposed Emera Brunswick Pipeline Through Saint John, NB," by Richard B. Kuprewicz, dated October 18, 2006.
14. "General Observations On the Myth of a Best International Pipeline Standard," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated March 31, 2007.
15. "Observations on Practical Leak Detection for Transmission Pipelines – An Experienced Perspective," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated August 30, 2007.
16. "Recommended Leak Detection Methods for the Keystone Pipeline in the Vicinity of the Fordville Aquifer," prepared for TransCanada Keystone L.P. by Richard B. Kuprewicz, President of Accufacts Inc., dated September 26, 2007.
17. "Increasing MOP on the Proposed Keystone XL 36-Inch Liquid Transmission Pipeline," prepared for the Pipeline Safety Trust by Richard B. Kuprewicz, dated February 6, 2009.
18. "Observations on Unified Command Drift River Fact Sheet No 1: Water Usage Options for the current Mt. Redoubt Volcano threat to the Drift River Oil Terminal," prepared for Cook Inletkeeper by Richard B. Kuprewicz, dated April 3, 2009.

19. "Observations on the Keystone XL Oil Pipeline DEIS," prepared for Plains Justice by Richard B. Kuprewicz, dated April 10, 2010.
20. "PADD III & PADD II Refinery Options for Canadian Bitumen Oil and the Keystone XL Pipeline," prepared for the Natural Resources Defense Council (NRDC), by Richard B. Kuprewicz, dated June 29, 2010.
21. "The State of Natural Gas Pipelines in Fort Worth," prepared for the Fort Worth League of Neighborhoods by Richard B. Kuprewicz, President of Accufacts Inc., and Carl M. Weimer, Executive Director Pipeline Safety Trust, dated October, 2010.
22. "Accufacts' Independent Observations on the Chevron No. 2 Crude Oil Pipeline," prepared for the City of Salt Lake, Utah, by Richard B. Kuprewicz, dated January 30, 2011.
23. "Accufacts' Independent Analysis of New Proposed School Sites and Risks Associated with a Nearby HVL Pipeline," prepared for the Sylvania, Ohio School District, by Richard B. Kuprewicz, dated February 9, 2011.
24. "Accufacts' Report Concerning Issues Related to the 36-inch Natural Gas Pipeline and the Application of Appleview, LLC Premises: 7009 and 7010 River Road, North Bergen, NJ," prepared for the Galaxy Towers Condominium Association Inc., by Richard B. Kuprewicz, dated February 28, 2011.
25. "Prepared Testimony of Richard B. Kuprewicz Evaluating PG&E's Pipeline Safety Enhancement Plan," submitted on behalf of The Utility Reform Network (TURN), by Richard B. Kuprewicz, Accufacts Inc., dated January 31, 2012.
26. "Evaluation of the Valve Automation Component of PG&E's Safety Enhancement Plan," extracted from full testimony submitted on behalf of The Utility Reform Network (TURN), by Richard B. Kuprewicz, Accufacts Inc., dated January 31, 2012, Extracted Report issued February 20, 2012.
27. "Accufacts' Perspective on Enbridge Filing to NEB for Modifications on Line 9 Reversal Phase I Project," prepared for Equiterre Canada, by Richard B. Kuprewicz, Accufacts Inc., dated April 23, 2012.
28. "Accufacts' Evaluation of Tennessee Gas Pipeline 300 Line Expansion Projects in PA & NJ," prepared for the Delaware RiverKeeper Network, by Richard B. Kuprewicz, Accufacts Inc., dated June 27, 2012.
29. "Impact of an ONEOK NGL Pipeline Release in At-Risk Landslide and/or Sinkhole Karst Areas of Crook County, Wyoming," prepared for landowners, by Richard B. Kuprewicz, Accufacts Inc., and submitted to Crook County Commissioners, dated July 16, 2012.
30. "Impact of Processing Dilbit on the Proposed NPDES Permit for the BP Cherry Point Washington Refinery," prepared for the Puget Soundkeeper Alliance, by Richard B. Kuprewicz, Accufacts Inc., dated July 31, 2012.
31. "Analysis of SWG's Proposed Accelerated EVPP and P70VSP Replacement Plans, Public Utilities Commission of Nevada Docket Nos. 12-02019 and 12-04005," prepared for the State of Nevada Bureau of Consumer Protection, by Richard B. Kuprewicz, Accufacts Inc., dated August 17, 2012.
32. "Accufacts Inc. Most Probable Cause Findings of Three Oil Spills in Nigeria," prepared for Bohler Advocaten, by Richard B. Kuprewicz, Accufacts Inc., dated September 3, 2012.
33. "Observations on Proposed 12-inch NGL ONEOK Pipeline Route in Crook County Sensitive or Unstable Land Areas," prepared by Richard B. Kuprewicz, Accufacts Inc., dated September 13, 2012.
34. "Findings from Analysis of CEII Confidential Data Supplied to Accufacts Concerning the Millennium Pipeline Company L.L.C. Minisink Compressor Project Application to FERC, Docket No. CP11-515-000," prepared by Richard B. Kuprewicz, Accufacts Inc., for Minisink Residents for Environmental Preservation and Safety (MREPS), dated November 25, 2012.
35. "Supplemental Observations from Analysis of CEII Confidential Data Supplied to Accufacts Concerning Tennessee Gas Pipeline's Northeast Upgrade Project," prepared by Richard B. Kuprewicz, Accufacts Inc., for Delaware RiverKeeper Network, dated December 19, 2012.

36. "Report on Pipeline Safety for Enbridge's Line 9B Application to NEB," prepared by Richard B. Kuprewicz, Accufacts Inc., for Equiterre, dated August 5, 2013.
37. "Accufacts' Evaluation of Oil Spill Joint Investigation Visit Field Reporting Process for the Niger Delta Region of Nigeria," prepared by Richard B. Kuprewicz for Amnesty International, September 30, 2013.
38. "Accufacts' Expert Report on ExxonMobil Pipeline Company Silvertip Pipeline Rupture of July 1, 2011 into the Yellowstone River at the Laurel Crossing," prepared by Richard B. Kuprewicz, November 25, 2013.
39. "Accufacts Inc. Evaluation of Transco's 42-inch Skillman Loop submissions to FERC concerning the Princeton Ridge, NJ segment," prepared by Richard B. Kuprewicz for the Princeton Ridge Coalition, dated June 26, 2014, and submitted to FERC Docket No. CP13-551.
40. Accufacts report "DTI Myersville Compressor Station and Dominion Cove Point Project Interlinks," prepared by Richard B. Kuprewicz for Earthjustice, dated August 13, 2014, and submitted to FERC Docket No. CP13-113-000.
41. "Accufacts Inc. Report on EA Concerning the Princeton Ridge, NJ Segment of Transco's Leidy Southeast Expansion Project," prepared by Richard B. Kuprewicz for the Princeton Ridge Coalition, dated September 3, 2014, and submitted to FERC Docket No. CP13-551.
42. Accufacts' "Evaluation of Actual Velocity Critical Issues Related to Transco's Leidy Expansion Project," prepared by Richard B. Kuprewicz for Delaware Riverkeeper Network, dated September 8, 2014, and submitted to FERC Docket No. CP13-551.
43. "Accufacts' Report to Portland Water District on the Portland – Montreal Pipeline," with Appendix, prepared by Richard B. Kuprewicz for the Portland, ME Water District, dated July 28, 2014.
44. "Accufacts Inc. Report on EA Concerning the Princeton Ridge, NJ Segment of Transco's Leidy Southeast Expansion Project," prepared by Richard B. Kuprewicz and submitted to FERC Docket No. CP13-551.
45. Review of Algonquin Gas Transmission LLC's Algonquin Incremental Market ("AIM Project"), Impacting the Town of Cortlandt, NY, FERC Docket No. CP14-96-0000, Increasing System Capacity from 2.6 Billion Cubic Feet (Bcf/d) to 2.93 Bcf/d," prepared by Richard B. Kuprewicz, and dated Nov. 3, 2014.
46. Accufacts' Key Observations dated January 6, 2015 on Spectra's Recent Responses to FERC Staff's Data Request on the Algonquin Gas Transmission Proposal (aka "AIM Project"), FERC Docket No. CP 14-96-000) related to Accufacts' Nov. 3, 2014 Report and prepared by Richard B. Kuprewicz.
47. Accufacts' Report on Mariner East Project Affecting West Goshen Township, dated March 6, 2015, to Township Manager of West Goshen Township, PA, and prepared by Richard B. Kuprewicz.
48. Accufacts' Report on Atmos Energy Corporation ("Atmos") filing on the Proposed System Integrity Projects ("SIP") to the Mississippi Public Service Commission ("MPSC") under Docket No. 15-UN-049 ("Docket"), prepared by Richard B. Kuprewicz, dated June 12, 2015.
49. Accufacts' Report to the Shwx'owhamel First Nations and the Peters Band ("First Nations") on the Trans Mountain Expansion Project ("TMEP") filing to the Canadian NEB, prepared by Richard B. Kuprewicz, dated April 24, 2015.
50. Accufacts Report Concerning Review of Siting of Transco New Compressor and Metering Station, and Possible New Jersey Intrastate Transmission Pipeline Within the Township of Chesterfield, NJ ("Township"), to the Township of Chesterfield, NJ, dated February 18, 2016.
51. Accufacts Report, "Accufacts Expert Analysis of Humberplex Developments Inc. v. TransCanada Pipelines Limited and Enbridge Gas Distribution Inc.; Application under Section 112 of the National Energy Board Act, R.S.C. 1985, c. N-7," dated April 26, 2016, filed with the Canadian Nation Energy Board (NEB).
52. Accufacts Report, "A Review, Analysis and Comments on Engineering Critical Assessments as proposed in



PHMSA's Proposed Rule on Safety of Gas Transmission and Gathering Pipelines," prepared for Pipeline Safety Trust by Richard B. Kuprewicz, dated May 16, 2016.

53. Accufacts' Report on Atmos Energy Corporation ("Atmos") filing to the Mississippi Public Utilities Staff, "Accufacts Review of Atmos Spending Proposal 2017 – 2021 (Docket N. 2015-UN-049)," prepared by Richard B. Kuprewicz, dated August 15, 2016.
54. Accufacts Report, "Accufacts Review of the U.S. Army Corps of Engineers (USACE) Environmental Assessment (EA) for the Dakota Access Pipeline ("DAPL")," prepared for Earthjustice by Richard B. Kuprewicz, dated October 28, 2016.
55. Accufacts' Report on Mariner East 2 Expansion Project Affecting West Goshen Township, dated January 6, 2017, to Township Manager of West Goshen Township, PA, and prepared by Richard B. Kuprewicz.
56. Accufacts Review of Puget Sound Energy's Energize Eastside Transmission project along Olympic Pipe Line's two petroleum pipelines crossing the City of Newcastle, for the City of Newcastle, WA, June 20, 2017.
57. Accufacts Review of the Draft Environmental Impact Statement for the Line 3 Pipeline Project Prepared for the Minnesota Department of Commerce, July 9, 2017, filed on behalf of Friends of the Headwaters, to Minnesota State Department of Commerce for Docket Nos. CN-14-916 & PPL-15-137.
58. Testimony of Richard B. Kuprewicz, president of Accufacts Inc., in the matter West Goshen Township and Concerned Citizens of West Goshen Township v. Sunoco Pipelines, L.P. before the Pennsylvania Public Utilities Commission, Docket No. C-2017-2589346, on July 18, 2017, on Behalf of West Goshen Township and Concerned Citizens of West Goshen Township.
59. Direct Testimony of Richard B. Kuprewicz, president of Accufacts Inc., on Behalf of Friends of the Headwaters regarding Enbridge Energy, Limited Partnership proposal to replace and reroute an existing Line 3 to the Minnesota Office of Administrative Hearings for the Minnesota Public Utilities Commission (MPUC PL-9/CN-14-916 and MPUC PL-9/PPL-15-137), September 11, 2017 and October 23, 2017.
60. Direct Testimony of Richard B. Kuprewicz On Behalf of The District of Columbia Government, before the Public Service Commission of the District of Columbia, in the matter of the merger of AltaGas Ltd. and WGL Holdings, Inc., Formal Case No. 1142, September 29, 2017.
61. Report to Mississippi Public Utilities Staff ("MPUS"), "Accufacts Review on Atmos Energy Corporation's Proposed Capital Budget for Fiscal Year 2018 related to System Integrity Program Spending (Docket N. 2015-UN-049)," prepared by Richard B. Kuprewicz, dated December 4, 2017.
62. Report to Hugh A. Donaghue, Esquire, Concord Township Solicitor, "Accufacts Comments on Adelphia Project Application to FERC (Docket No. CP18-46-000) as it might impact Concord Township," dated May 30, 2018.
63. Report to Mississippi Public Utilities Staff ("MPUS"), "Accufacts Review on Atmos Energy Corporation's Proposed Capital Budget for Fiscal Year 2019 related to System Integrity Program Spending (Docket N. 2015-UN-049)," prepared by Richard B. Kuprewicz, dated August 20, 2018.
64. Report to West Goshen Township Manager, PA, "Accufacts report on the repurposing of an existing 12-inch Sunoco pipeline segment to interconnect with the Mariner East 2 and Mariner East 2X crossing West Goshen Township," dated November 8, 2018.
65. Report to West Whiteland Township Manager, PA, "Accufacts Observations on Possible Pennsylvania State Pipeline Safety Regulations," prepared by Richard B. Kuprewicz, dated March 22, 2019.
66. Accufacts Public Comments on the Proposed Joint Settlement, BI&E v. Sunoco Pipeline L.P. ("SPLP"), Docket No. C-2018-3006534 ("Proposed Settlement"), submitted on August 15, 2019 to the Pennsylvania Public Utility Commission on the behalf of West Goshen Township as an intervener.
67. Report to West Whiteland Township Manager, Ms. Mimi Gleason, "Accufacts Perspective on Two Questions from West Whiteland's Board of Supervisors on Proposed Changes to ME 2 and ME 2X Construction/Operational Activities within West Whiteland," dated September 5, 2019."

68. Report to West Goshen Township Manager, Mr. Casey LaLonde, "Accufacts Report on the episode on the evening of 8-5-19 at the Mariner East Boot Road Pump Station ("Event"), Boot Road, West Goshen Township, PA," dated September 16, 2019.
69. Provided direct testimony before the Arizona Corporation Commission, In the Matter of the Application of Southwest Gas Corporation for the Establishment of Just and Reasonable Rates and Charges Designed to Realize a Reasonable Rate of Return on Fair Value of the Properties of Southwest Gas Corporation Devoted to its Arizona Operations (Docket No. G-01551A-19-0055), testified on behalf of Utilities Division Arizona Corporation Commission, February 19, 2020.
70. Report to West Goshen Township Manager, Mr. Casey LaLonde, "Accufacts Report on the Mariner East 2X Pipeline Affecting West Goshen Township," dated July 23, 2020.
71. Assisted the Commonwealth of Massachusetts, Office of the Attorney General in developing pipeline safety processes to be incorporated into the settlement agreement related to Columbia Gas' sale of Assets to Eversource following the Merrimack Valley, Massachusetts overpressure event of September 13, 2018.
72. Report to Natural Resources Defense Council, Inc., "Accufacts' Observations on the Use of Keystone XL Pipeline Pipe Exhibiting External Coating Deterioration Issues from Long Term Storage Exposure to the Elements," October 1, 2020.
73. Report to Pennsylvania Public Utilities Commission ("PAPUC"), "Accufacts Comments on Proposed Pennsylvania Intrastate Liquid Pipeline Safety Regulations," dated October 29, 2021, prepared for West Whiteland Township Board of Supervisors, West Whiteland Township, PA. Filed to PAPUC public web docket November 5, 2021 by West Whiteland Township under Reference Docket Number L-2019-3010267. Addresses suggested improvements in proposed pipeline safety rules for PA intrastate liquid transmission pipelines.
74. Submitted written testimony of Richard B. Kuprewicz on Behalf of Bay Mills Indian Community to ALJ Dennis Mack, dated December 14, 2021, in the matter of the Application of Enbridge Energy, Limited Partnership for Authority to Replace and Relocate the Segment of Line 5 Crossing the Straits of Mackinac into a Tunnel Beneath the Straits of Mackinac, before the State of Michigan Public Service Commission, U-20763.
75. Public presentation to New York State Indian Point Nuclear Facility Decommissioning Oversight Board on Holtec removal activities in proximity to Enbridge three Natural Gas Transmission Pipelines, March 17, 2022.
76. Report to Pipeline Safety Trust and Bold Alliance, "Accufacts' Perspectives on the State of Federal Carbon Dioxide Transmission Pipeline Safety Regulations as it Relates to Carbon Capture, Utilization, and Sequestration within the U.S.," March 23, 2022.
77. Accufacts Inc., Public Presentation For the National Academies of Science Engineering Medicine and The Transportation Research Board, "To Committee on Criteria for Installing Automatic and Remote-Controlled Shutoff Valves on Existing Gas and Hazardous Liquid Transmission Pipelines," 4/27/22.
78. Accufacts Inc, "6/13/22 Webinar to Illinois Emergency Responders, Healthcare Providers, & Local Officials on Responses to CO<sub>2</sub> Transmission Pipeline Releases," 6/13/22.
79. Accufacts Report for Pipeline Safety Trust, "Safety of Hydrogen Transportation by Gas Pipelines," 11/28/22.

**Accufacts Inc.**

“Clear Knowledge in the Over Information Age”

**Accufacts’ Perspectives on the State of Federal Carbon Dioxide Transmission Pipeline Safety Regulations as it Relates to Carbon Capture, Utilization, and Sequestration within the U.S.**

prepared for the

**Pipeline Safety**



T R U S T

<http://www.pstrust.org/>

Credible.  
Independent.  
In the public interest.

by

**Richard B. Kuprewicz**  
President, Accufacts Inc.  
[kuprewicz@comcast.net](mailto:kuprewicz@comcast.net)  
March 23, 2022

**This report is developed from information clearly in the public domain. The views expressed in this document represent the opinion of the author.**

## I. Introduction

Accufacts Inc. (“Accufacts”) was asked to review and comment on various aspects related to carbon dioxide transmission pipeline safety and federal pipeline safety regulations within the U.S. In recent years there has been considerable discussion about how to address carbon dioxide emissions and global warming through carbon capture, utilization, and sequestration (aka “CCUS” or “CCS”). CCS efforts are intended to help mitigate climate change by capturing carbon dioxide emissions both before and after they are released to the atmosphere and permanently storing such material deep in underground geological structures.

The federal Pipeline Safety Act (“PSA”) directs the U.S. Department of Transportation (“DOT”) to issue detailed safety standards with regard to the design, construction, operation, and maintenance of CO<sub>2</sub> pipelines.<sup>1, 2</sup> In turn, the DOT has delegated its authority to the Pipeline and Hazardous Materials Safety Administration (“PHMSA”). The PSA’s broad mandate is supplemented by detailed federal regulations.<sup>3</sup> The PSA expressly prohibits state and local regulation that interferes with or supplements federal safety standards for interstate pipelines.<sup>4</sup> States meeting certain conditions may supplement federal pipeline safety regulation on their intrastate pipelines as long as such state regulations are not in conflict with federal pipeline safety regulations.

The U.S. has the most mileage of CO<sub>2</sub> transmission pipelines in the world, consisting of approximately 5,150 miles, out of a total 229,287 miles of hazardous liquid transmission pipelines within the U.S.<sup>5</sup> The vast majority, if not all, of these CO<sub>2</sub> existing pipelines are driven by enhanced oil recovery (“EOR”) efforts that increase oil production utilizing CO<sub>2</sub> in a supercritical state. Most of this supercritical state CO<sub>2</sub> comes from high pressure higher purity natural underground source domes. It is an excellent solvent for EOR efforts, but the CO<sub>2</sub> must be injected into oil fields as a supercritical fluid.

CCS efforts are driven by an entirely different purpose such that CO<sub>2</sub> used for CCS could be shipped as a gas or a non-supercritical liquid. However, current federal safety regulations regulate only pipelines that transport supercritical CO<sub>2</sub> containing over 90% carbon dioxide molecules, and not pipelines that ship CO<sub>2</sub> in these other lower concentrations or forms, leaving a large regulatory gap. Moreover, even the regulations for supercritical CO<sub>2</sub> pipelines are incomplete or inadequate and place the public at

---

<sup>1</sup> 49 U.S.C. § 60101 *et seq.*

<sup>2</sup> 49 U.S.C. § 60102(a) and (i).

<sup>3</sup> 49 C.F.R. Part 195.

<sup>4</sup> 49 U.S.C. § 60104(c) (“A State authority may not adopt or continue in force safety standards for interstate pipeline facilities or interstate pipeline transportation.”)

<sup>5</sup> PHMSA reporting database, “Hazardous Liquid Pipeline Miles and Tanks,” as of January 31, 2022 for CO<sub>2</sub> commodity at:

[https://portal.phmsa.dot.gov/analytics/saw.dll?Portalpages&PortalPath=%2Fshared%2FPDM%20Public%20Website%2F\\_portal%2FPublic%20Reports&Page=Infrastructure](https://portal.phmsa.dot.gov/analytics/saw.dll?Portalpages&PortalPath=%2Fshared%2FPDM%20Public%20Website%2F_portal%2FPublic%20Reports&Page=Infrastructure).

great risk, especially from the tens of thousands of miles of CO<sub>2</sub> pipelines that may be driven by CCS efforts.<sup>6</sup>

A flurry of multibillion dollar CO<sub>2</sub> pipeline proposals have recently been announced, likely driven by enhanced tax credit incentives provided by Internal Revenue Code § 45Q.<sup>7,8,9</sup> Congress provided these enhancements in the Bipartisan Budget Act of 2018, and expanded by the Infrastructure Investment and Jobs Act of 2021 (“Acts of 2018 and 2021”).<sup>10</sup> As intended, these laws accelerated CCS and CO<sub>2</sub> pipeline development efforts, because they make such credits more available and valuable to certain generators of CO<sub>2</sub> emissions and require projects to start construction by January 1, 2026.<sup>11</sup> Since most carbon dioxide emitters are likely considerable distances from suitable deep, permanent underground storage sites, it is understandable that CO<sub>2</sub> transmission pipelines may be needed between emitters and these storage sites. If CO<sub>2</sub> pipeline mileage increases as projected, the CO<sub>2</sub> pipeline network could soon rival the existing oil and natural gas pipeline networks in size and complexity. PHMSA would be faced with the greatest and fastest pipeline expansion in the history of the U.S. pipeline industry, and many of these pipelines could threaten the safety of countless individuals and communities.

This report is intended to increase regulator and public awareness of the regulatory challenges posed by this proposed massive expansion in CO<sub>2</sub> pipeline mileage and the unique safety risks of transporting CO<sub>2</sub>, especially in its supercritical state. It focuses on a higher-level review of the more technical pipeline safety matters, based on decades of pipeline safety experience including pipeline failure investigations, process engineering and process safety management practice, as well as years of experience in processing and handling many tons of liquid CO<sub>2</sub>. This report also makes specific recommendations for improvements in federal pipeline safety regulations needed to fill regulatory gaps and ensure public safety. The proposed CO<sub>2</sub> pipeline boom presents

---

<sup>6</sup> For one perspective see what I would call a planning study from Princeton University, “Net-Zero America - Potential Pathways, Infrastructure, and Impacts,” Final Report, October 29, 2021, pp. 212 – 219 of 348, indicating a possible need of over 60,000 new miles of CO<sub>2</sub> pipelines by 2050.

<sup>7</sup> Des Moines Register, “What we know about two carbon capture pipelines proposed in Iowa,” <https://www.desmoinesregister.com/story/money/business/2021/11/28/what-is-carbon-capture-pipeline-proposals-iowa-ag-ethanol-emissions/8717904002/>, Nov. 28, 2021.

<sup>8</sup> Agweek, “World’s largest carbon capture pipeline aims to connect 31 ethanol plants, cut across Upper Midwest,” <https://www.agweek.com/business/worlds-largest-carbon-capture-pipeline-aims-to-connect-31-ethanol-plants-cut-across-upper-midwest> 12/6/2021.

<sup>9</sup> S&P Global Platts, “Oil producer Denbury plans CO<sub>2</sub> storage hub in southern Alabama,” <https://www.spglobal.com/platts/en/market-insights/latest-news/energy-transition/020822-oil-producer-denbury-plans-co2-storage-hub-in-southern-alabama>, 2/8/2022.

<sup>10</sup> 26 U.S.C. § 45Q.

<sup>11</sup> I.R.C. § 45Q.

PHMSA with an unprecedented challenge; hopefully, this report will help PHMSA rise to this challenge.

## II. A brief history of U.S. federal CO<sub>2</sub> pipeline safety regulation

PHMSA and its predecessor agencies, such as the Office of Pipeline Safety, have historically relied on more prescriptive minimum safety approaches. In the past several decades federal minimum pipeline safety regulations have, by the industry's lobbying, shifted to more "performance-based" approaches that rely heavily on certain industry standards or recommended practices, some of which are incorporated by reference into federal pipeline safety regulation.<sup>12</sup> This industry driven shift can result in changes in pipeline safety regulations without proper public input. A prime example may be in the development of CO<sub>2</sub> transmission pipeline safety regulations that historically have been a very small percentage of overall transmission pipeline mileage in the U.S. This country may be facing a significant increase in CO<sub>2</sub> transmission pipeline mileage without appropriate pipeline safety regulatory development or enactment, leaving the country and the public ill prepared for a tsunami of CO<sub>2</sub> pipeline construction.

Congress, in Section 211 of the Pipeline Safety Reauthorization Act of 1988, required that the DOT regulate carbon dioxide transported by pipeline facilities. Part of this concern was driven by a 1986 natural carbon dioxide release event in Lake Nyos, Cameroon spanning many miles with over 1,700 fatalities, underscoring the dangers and possible consequences of CO<sub>2</sub> releases.<sup>13</sup> On July 12, 1991, federal regulators issued a minimalist final rule that mainly added the words "and carbon dioxide" to existing federal minimum pipeline safety regulations developed for hazardous liquid petroleum pipelines (49CFR§195). It opted to not issue standards specifically applicable to supercritical CO<sub>2</sub> pipelines due to the small number of already existing and anticipated CO<sub>2</sub> pipelines. Even though the situation is about to change dramatically, PHMSA has not proposed to review and overhaul its CO<sub>2</sub> pipeline standards, such that these limited regulations are still in effect today.<sup>14</sup> As a result, many of PHMSA's regulations no longer are adequate to protect public safety.

For example, under federal regulations "carbon dioxide" is defined as follows:

"Carbon Dioxide means a fluid consisting of more than 90 percent carbon dioxide molecules compressed to a supercritical state."<sup>15</sup>

---

<sup>12</sup> 49CFR§195.3 What documents are incorporated by reference partly or wholly in this part?

<sup>13</sup> Federal Register / Vol. 56, No. 113 / Wednesday, June 12, 1991/Rules and Regulations, Research and Special Programs Administration (RSPA), DOT, Docket No. PS-112, Amendment 195-45, RIN 2137-AB72, 49CFR Part 195, "Transportation of Carbon Dioxide by Pipeline," final rule.

<sup>14</sup> *Ibid*, p. 26924.

<sup>15</sup> 49CFR§195.2 Definitions.

The above definition is clearly not appropriate to deal with CCS CO<sub>2</sub> pipelines, nor is that its intent as demonstrated further in this report.

Existing U.S. CO<sub>2</sub> transmission pipelines are primarily located in sparsely developed or more rural locations and, as mentioned previously, involve approximately 5,150 miles moving CO<sub>2</sub> mostly from natural underground sources/domes to EOR projects. The current definition of “carbon dioxide” does not include pipelines that transport supercritical carbon dioxide streams in which CO<sub>2</sub> makes up less than 90 percent of the stream. It also excludes pipelines that transport CO<sub>2</sub> as a non-supercritical liquid or gas. In 1991, there were only a very limited number of pipelines transporting CO<sub>2</sub> in these other forms that apparently didn’t justify the need for federal regulation, which is not the case now.

In 2011, Congress, in the Pipeline Safety, Regulatory Certainty, and Job Creation Act of 2011, Section 15, mandated that the Secretary of Transportation “prescribe minimum safety standards for the transportation of carbon dioxide by pipeline in a gaseous state.” As a result, PHMSA issued a report in early 2015 entitled “Background for Regulating the Transportation of Carbon Dioxide in a Gaseous State.”<sup>16</sup> Unfortunately, PHMSA never issued new regulations for transportation of CO<sub>2</sub> as a gas.

Thus, PHMSA currently has no regulations applicable to pipelines transporting CO<sub>2</sub> as a gas, liquid, or in a supercritical state at concentrations of CO<sub>2</sub> less than 90 percent. This regulatory gap means that current federal pipeline safety regulations are clearly inadequate because CO<sub>2</sub> pipeline companies could develop CO<sub>2</sub> gas and liquid pipelines that fall outside of this narrow federal rule. The definition of “carbon dioxide” should be modified so that all CO<sub>2</sub> transmission pipelines are regulated by federal law and held to appropriate minimum safety standards. Otherwise, CO<sub>2</sub> pipelines could be designed, constructed, operated, and maintained with no federal or state oversight.

### **III. CO<sub>2</sub> transmission pipelines can take on three basic forms**

CO<sub>2</sub> transmission pipelines can be designed to transport carbon dioxide either as a supercritical state fluid, a liquid (aka in a subcritical or chilled state), or as a gas. Within the industry the term “dense phase” is often used to label CO<sub>2</sub> pipelines operating in either a supercritical state fluid or in a liquid phase as explained below. It is odd that the proposed new CO<sub>2</sub> transmission pipeline applications recently reviewed have not clearly stated in what phase they are designed to operate, their temperature ranges, nor their quality requirements.<sup>17</sup> The key characteristics of supercritical, liquid, and gaseous CO<sub>2</sub> transmission pipelines are summarized below.

---

<sup>16</sup> PHMSA report dated February 2015, posted to the 2016 docket under PHMSA-2016-0049-001 at [www.regulations.gov](http://www.regulations.gov).

<sup>17</sup> For example, see Summit Carbon Solutions, “Application to the South Dakota Public Utilities Commission for a Permit for the SCS Carbon Transport LLC (SCS) Pipeline Under the Energy Conversion and Transmission Facility Act – Document Number: SCS-0700-ENV-05-PE-009-A,” dated February 7, 2022.

**i. Supercritical state CO<sub>2</sub> transmission pipelines**

Pure CO<sub>2</sub> has a critical temperature of about 88 °F (33 °C) and a critical pressure of approximately 1070 psia, or pounds force per square inch absolute (73 atm). At temperatures and pressures above these critical values, CO<sub>2</sub> is not technically a liquid and instead is in a supercritical state as a dense phase “fluid” or vapor with properties between that of a liquid and a gas. This supercritical fluid will not condense to liquid within the pipeline, as long as the temperature remains above the critical temperature, no matter how high the pressure is increased above the critical pressure. If the temperature along a supercritical state pipeline drops below the critical temperature, part of the fluid will condense to liquid with a higher density than the fluid. If the pressure along a supercritical state pipeline drops below 1070 psia, part of the CO<sub>2</sub> will convert to a gas/liquid mixture depending on the temperature.

The primary reason that the existing 5,000 or so miles of CO<sub>2</sub> pipelines transport CO<sub>2</sub> in a supercritical state is because CO<sub>2</sub> in this state is an excellent solvent having no liquid surface tension. It readily dissolves oil trapped in porous rock. In contrast, CO<sub>2</sub> destined for sequestration could be transported as a gas or liquid, because sequestration does not, as a practical matter, need the CO<sub>2</sub> to be in a supercritical state, and federal law does not require transportation in a supercritical state. In fact, a clever pipeline operator could employ loopholes to avoid federal pipeline safety oversight by PHMSA. Clearly the sources and needs of CO<sub>2</sub> for EOR are not the same as those for the CCS objective, which is to remove CO<sub>2</sub> from the atmosphere.

CO<sub>2</sub> supercritical fluid transmission pipeline operating pressures usually range from 1,200 to 2,200 pounds force per square inch gauge, or psig. The higher pressure is set based on the maximum operating pressure (“MOP”) usually related to a pipe specification limit.<sup>18</sup> There are a minor number of CO<sub>2</sub> supercritical state pipelines that have been designed to operate at much higher MOPs (*e.g.*, 3200 psig). Moving CO<sub>2</sub> as a dense phase supercritical state fluid permits the use of pumps along a pipeline instead of compressors that would be needed to move the material if it were a gas. For pipelines, the use of pumps to move higher density fluids requires smaller, less complex, equipment that is more efficient in moving mass along a pipeline than compressors (*i.e.*, pumps are cheaper to build, install, maintain, and operate than compressors). In addition, the higher MOPs of supercritical state CO<sub>2</sub> pipelines permit them to utilize smaller diameter pipe, albeit much stronger pipe, to move the same tonnage of CO<sub>2</sub> as compared to shipment as a gas. In contrast, gas pipelines require larger diameter pipe to move the same tonnage, because they must usually operate at pressures lower than the supercritical pressure (1070 psig), otherwise some of the CO<sub>2</sub> could convert to a liquid

---

<sup>18</sup> MOP stands for maximum operating pressure for liquid pipelines and is defined in federal minimum pipeline safety regulations that provide conditions for “normal” operation of pipelines. Pipelines are permitted to exceed MOP within certain limits, under certain situations.



(depending on the temperature along the pipeline) and such liquid slugs would severely damage/destroy the compressors used in gas pipelines.

While there are many cost/efficiency advantages to moving CO<sub>2</sub> in a supercritical state, there is one well known threat associated with supercritical state operation. A CO<sub>2</sub> pipeline operating in a supercritical state can be more prone to pipe running ductile fractures than hazardous liquids or natural gas pipelines. Running ductile fractures are unusual and particularly dangerous fractures that can “unzip” a CO<sub>2</sub> transmission pipeline for extended distances exposing great lengths of the buried pipeline. These extreme rupture forces throw tons of pipe, pipe shrapnel, and ground covering, generating large craters along the failed pipeline. It is well known that CO<sub>2</sub> pipelines operating in dense phase, either supercritical or as a liquid, are particularly susceptible to such running ductile fractures. Although current federal regulations recognize this risk, they do not contain any detailed requirements that specifically identify how to address fracture propagation threats. Though there are various approaches well known in the industry (*i.e.*, pipe steel fracture toughness parameters, usually for new pipe, and/or mechanical arrestors such as valves, thicker/tougher pipe transitions) such approaches should be specifically mentioned in safety regulation.<sup>19</sup> To address this risk, PHMSA should revise federal regulations, especially for supercritical CO<sub>2</sub> pipelines, to specifically mitigate the effects of these fracture propagation forces. The current regulations do not adequately address these CO<sub>2</sub> fracture risks.

**ii. Liquid CO<sub>2</sub> transmission pipelines**

Subcooled or subcritical state means to transport CO<sub>2</sub> as a liquid that usually requires chilling and/or cooling of the stream slightly below ambient temperatures to assure the pipeline is operated in one phase, that of a liquid. For new pipelines this also may require the use of pipeline insulation, though not always, to reduce temperature increase of the CO<sub>2</sub> along the pipeline, assuring it stays as a liquid. It is important that cooling stay well above the pipe carbon steel brittle transition temperature of approximately - 20 °F to avoid the threat of catastrophic pipeline rupture. Despite these obstacles, transporting CO<sub>2</sub> as a liquid, basically at its highest density, which is typically about double the density of CO<sub>2</sub> fluid in its supercritical state, allows the pipeline transportation of more tonnage of carbon dioxide with even smaller diameter pipe than a supercritical state operation, as well as lower MOPs. Because the liquid phase operation also has a lower viscosity, a liquid CO<sub>2</sub> pipeline system for a given length can utilize a fewer number of pump stations that can have major advantages over supercritical state or gas pipeline approaches needed to move similar tonnage of CO<sub>2</sub>. For CCS objectives, liquid phase CO<sub>2</sub> transmission pipelines additional efficiency over their supercritical state or gas counterparts may justify the additional cooling infrastructure along such

---

<sup>19</sup> 49 CFR§195.111 Fracture propagation. The regulation states in full: “A carbon dioxide pipeline system must be designed to mitigate the effects of fracture propagation.” Thus, pipeline safety law contains no detailed standards to prevent running ductile fractures leaving much room for misinterpretation.

pipelines. It is worth emphasizing that PHMSA chose to not issue regulations for CO<sub>2</sub> pipelines designed to operate as a liquid, so such pipelines are currently unregulated.

### **iii. CO<sub>2</sub> gas transmission pipelines**

New pipelines designed to move CO<sub>2</sub> as a gas in a transmission pipeline is not likely, given that the system must be operated at lower pressures. For a CO<sub>2</sub> gas pipeline, the MAOP must not exceed approximately 1,000 psig at normal operating temperatures, so that the CO<sub>2</sub> is maintained as a gas and does not convert to a liquid as this could be disastrous for the pipeline's compressors.<sup>20</sup> For an equivalent daily CO<sub>2</sub> tonnage pipeline capacity, the requirement to keep design pressure lower drives such new gas pipeline approaches to much higher pipe diameters than their liquid or supercritical state pipeline alternatives. However, specific situations may exist where existing liquid or larger diameter natural gas pipelines could be "repurposed" into primarily CO<sub>2</sub> gas service.<sup>21</sup> Such change in service, will most likely be highly limited in its pipeline mileage and, in my opinion, should exceed the requirements identified in ADB-2014-04, addressing repurposing of natural gas pipelines or liquid pipelines. For example, an Advisory Bulletin, or ADB, does not carry the force of promulgated pipeline safety regulation but is issued to more quickly alert pipeline operators of PHMSA concerns on certain issues. ADB-2014-04 does not address, nor was it intended to address, the specific additional challenges associated with unique fracture propagation risks associated with CO<sub>2</sub> transmission pipelines as previous discussed. While there are unique situations where nonoperating or underutilized pipelines exist, there are several factors that can make repurposing of such pipelines to CO<sub>2</sub> gas service economically attractive, given the billions of dollars in tax credit incentives associated with CCS under the Acts of 2018 and 2021, and the associated start construction deadline. The critical deadlines to meet tax credit triggers could make timing of such conversions more favorable than routing and construction of new CO<sub>2</sub> pipelines for CCS. Such pipeline conversions would be at much greater risk of failure from CO<sub>2</sub> service than conventional hydrocarbon or new construction CO<sub>2</sub> pipelines, given the unique and increased potential for CO<sub>2</sub> pipeline ruptures from various risks associated with CO<sub>2</sub> operation. Only time will tell, given the economic temptations and timing thresholds, whether such repurposing of an existing transmission pipeline to CO<sub>2</sub> service will prove practical for CCS utilization.

---

<sup>20</sup> MAOP stands for maximum allowable operating pressure, which is the standard for gas pipelines and is defined in federal minimum pipeline safety regulations that provide conditions for "normal" operation of pipelines. Pipelines are permitted to exceed MAOP within certain limits, under certain situations.

<sup>21</sup> See DOT PHMSA, Advisory Bulletin, ADB-2014—04, "Pipeline Safety: Guidance for Pipeline Flow Reversals, Product Changes and Conversion to Service," Docket No. PHMSA-2014-0040, Sept 12, 2014.

#### **IV. CO<sub>2</sub> transmission pipelines pose different risks than traditional hydrocarbon transmission pipelines**

Carbon dioxide gas is odorless, colorless, doesn't burn, is heavier than air, and is an asphyxiant and intoxicant, making CO<sub>2</sub> pipeline releases harder to observe and avoid especially as a released plume spreads and migrates well off the pipeline right-of-way. CO<sub>2</sub> properties differ from those for materials moved in hazardous hydrocarbon liquid or natural gas transmission pipelines. CO<sub>2</sub> pipeline releases significantly increase the possible "affected" or "potential impact" area identified in federal regulations addressing hydrocarbon transmission pipelines upon pipeline rupture release, and CO<sub>2</sub> pipeline ruptures have a greater potential to endanger the public. Current federal pipeline safety regulations do not incorporate these important CO<sub>2</sub> differences to assure safety to the public. Federal pipeline safety regulatory changes are warranted if CO<sub>2</sub> pipeline mileage is to be increased dramatically in the U.S., especially under CCS. CO<sub>2</sub> transmission pipelines have many unique failure dynamics such that a rupture may impact significantly greater geographic areas than hydrocarbon pipelines. In particular, a combination of CO<sub>2</sub> phase/temperature changes may result in explosive pipe release forces as the CO<sub>2</sub> converts to gas. Moreover, CO<sub>2</sub>'s lack of odor and invisibility means that it may not be possible for citizens and first responders to determine if they are in a hazard area before they are harmed, unless they have access to a CO<sub>2</sub> detection meter. It is important that anyone using such CO<sub>2</sub> detection meters assure that such equipment has been properly calibrated/maintained and users properly trained in their use and limitations. Once a CO<sub>2</sub> pipeline release has been warmed by the surrounding environment, it travels unseen influenced by gravity, terrain, and the wind, preferentially settling in low spots, displacing air and providing no warning to persons and animals caught in the invisible release plume. Hydrocarbon pipeline releases that haven't ignited, can usually be detected by unusual smell or sight, which makes CO<sub>2</sub> pipeline releases different and harder to detect by emergency responders or the public.

During a CO<sub>2</sub> pipeline rupture release, multiple phase changes can result not only in the significant lowering of temperature near the pipe failure site, but also the likelihood of solid CO<sub>2</sub> formation (i.e., dry ice). Dry ice particles within the fluid can contribute to fogging in the air and ground around the pipeline release, as well as the formation of dry ice within the pipeline upstream/downstream of the pipe failure site that can impact the rate of release out of a pipe failure. Such dry ice blockage can result in temporary restriction/blockage within the pipe, affecting release rate, especially for smaller diameter transmission pipelines experiencing rupture fracture.

In CO<sub>2</sub> pipelines experiencing smaller, slower rate releases, often called leaks, such as through minor holes or cracks, the resulting lower rate CO<sub>2</sub> rich clouds may disperse/dissipate after a short time. In much larger rate releases, such as pipeline rupture fractures caused from various anomalies or pipeline threats, the resulting release of cold gas and dry ice solid mixtures can be quite dangerous (see video of

DNV rupture failure test of an CO<sub>2</sub> 8-inch diameter pipeline).<sup>22</sup> The CO<sub>2</sub> released from a pipeline will be heavier than air, and the high-rate release from a pipe rupture will form cold dense gas fog clouds comprised of dry ice particles and visible water vapor as the humidity in the air condenses from the extreme cooling. Such high-rate releases can produce areas of low visibility from “fog,” both from dry ice particles and water condensation. The CO<sub>2</sub> pipeline rupture fog becomes transparent when eventually warmed by the surrounding environment. Upon warming, the CO<sub>2</sub> plume can flow considerable distances from the pipeline unobserved, traveling over terrain, displacing oxygen while settling or filling in low spots. Oxygen displacement can starve gasoline or diesel powered equipment, such as first responder and private vehicles, causing such equipment to malfunction or even shut off, and cause pilot lights on furnaces, stoves, and natural gas fireplaces to go out. Oxygen displacement by CO<sub>2</sub> gas can cause asphyxiation of humans and animals, that can lead to death. Further, CO<sub>2</sub> gas can cause disorientation, confusion, and unconsciousness, which can be dangerous for persons caught in the plume, especially those who are driving, using power equipment, or exposed to cold weather. Cooling of a CO<sub>2</sub> release can also impact the rate of release and exacerbate pipe fracture propagation during rupture. Clearly, dispersion modeling for analyzing potential impact areas for CO<sub>2</sub> pipeline failures and their related released gas plumes, must consider the propensity of heavier than air CO<sub>2</sub> gas to displace oxygen and to follow the terrain as terrain factors can play a critical role in evaluating a potential area and receptors that could be affected by a CO<sub>2</sub> pipeline release. It is vitally important to not underestimate the potential distance that a CO<sub>2</sub> pipeline rupture plume can reach and affect, especially in nonlevel terrain. Additional safety margins should be employed in populated areas when using dispersion modeling results for CO<sub>2</sub> pipeline releases.

Before the U.S. is blanketed with a major increase in CO<sub>2</sub> transmission pipeline mileage driven by CCS efforts, substantial changes need to be implemented in federal pipeline safety regulations specifically addressing the unique dangers of CO<sub>2</sub> in transmission pipelines in any phase. CO<sub>2</sub> is not flammable. It doesn't burn or explode/detonate from ignition, so heat radiation is not an issue of concern as in conventional hydrocarbon pipelines. CO<sub>2</sub> can, however, generate similar overpressure “blast” forces upon pipeline rupture (from the high-rate releases associated with pipeline fracture failure, see previous referenced 8-inch CO<sub>2</sub> pipeline rupture test). CO<sub>2</sub> pipeline rupture and resulting rapid “blast like” expansion forces dissipate quickly with distance from the pipeline but can easily extend well beyond the pipeline right of way. The areas potentially impacted by ruptures of oil and gas transmission pipelines are well defined in current federal regulations, which estimate how far liquid hydrocarbon will spread and the blast or burn radius resulting from a natural gas pipeline rupture. The danger zone for human life for hazardous hydrocarbon liquid and natural gas pipeline releases is generally measured in feet, albeit many thousands of feet for larger diameter higher pressure pipelines.

---

<sup>22</sup> Video of 2013 DNV Spadeadam Research and Testing test experiment of dense phase CO<sub>2</sub> 8-inch buried pipeline rupture, <https://www.dnv.com/oilgas/laboratories-test-sites/dense-phase-spadeadam-video.html>.

In contrast, a CO<sub>2</sub> pipeline's impact area may be measured in miles, not feet. This is likely because:

- CO<sub>2</sub> pipeline ruptures can release many tons of CO<sub>2</sub>,
- the compressed CO<sub>2</sub> will expand into gas phase upon pipeline rupture and fill a much larger volume than it did inside the pipe, and
- the CO<sub>2</sub> may not disperse quickly because it is heavier than air, meaning that it will tend to flow toward and settle in low lying areas including ravines, valleys, and basements.

Current federal pipeline safety regulations do not provide any methodology for assessing the hazard zone for CO<sub>2</sub> pipelines or require that pipeline operators adequately address this risk.

## V. Impact of impurities on CO<sub>2</sub> pipelines

The amounts and types of impurities in a CO<sub>2</sub> stream can have an impact on pipeline design and approaches. Current CO<sub>2</sub> pipeline regulations, which only address CO<sub>2</sub> pipelines greater than 90% CO<sub>2</sub> concentration compressed to a supercritical state, make no mention as to the level of non-CO<sub>2</sub> impurities such as H<sub>2</sub>S, which can be lethal even in very low parts per million concentrations. Also, impurities can affect the range of safe operating pressures. Most of the natural sources of CO<sub>2</sub> for existing pipelines contain CO<sub>2</sub> well above 90%, but this may not be the case for all CO<sub>2</sub> streams captured from industrial facilities. Federal regulation should be modified to adequately regulate CO<sub>2</sub> pipelines used for CCS, and subsequent transportation by transmission pipeline, especially because CCS pipelines may operate differently from those used for EOR. Such federal regulatory improvements should focus on public safety for all forms/phases of CO<sub>2</sub> transmission pipelines. There are some very pure sources of CO<sub>2</sub> emitters, such as ethanol plants and some hydrogen reformers, that emit very high concentrations of CO<sub>2</sub> to the atmosphere that require very little, if any, impurity treatment to prepare for pipeline transportation for CCS.<sup>23</sup> Unlike most of the currently existing CO<sub>2</sub> pipelines whose sources are underground natural gas domes or reservoirs, CSS pipelines may be supplied from various sources where the concentration of CO<sub>2</sub> is quite low and needing concentration, processing, and treatment for contaminant removal before it may be safely transported by pipeline.

There appears to be no transmission pipeline in the U.S. that transports pure CO<sub>2</sub>, although there are pipelines that move very high concentrations of CO<sub>2</sub>, well above 90%, containing only small levels, of impurities, especially those from natural sources of CO<sub>2</sub>. Such CO<sub>2</sub> rich sources can still contain impurities, such as hydrogen sulfide, methane, carbon monoxide, oxygen, nitrogen oxide, sulphur oxide, hydrogen, or

---

<sup>23</sup> My experience is that purity from such CO<sub>2</sub> specialized emitters can exceed 99.9 % with trace impurities.

water.<sup>24</sup> The types and amounts of impurities in a CO<sub>2</sub> rich pipeline is largely driven by the source of CO<sub>2</sub>, and proper operation of associated upstream treatment equipment to assure the material meets pipeline quality specifications, which is not always assured. At relatively low levels of impurities, such as at trace or levels in the lower parts per million, the specific effects of the impurities on the overall stream critical thermodynamic properties (such as enthalpy, entropy, density, and viscosity), are not significantly impacted. However, higher impurity concentrations, such as impurities measured in percentage concentrations should not be ignored as they can impact the critical pressure, but more importantly the critical temperature, such that even a percent or two change in impurity levels can result in unexpected phase change from dense phase fluid to other phases. Such phase changes may impact the system hydraulics, and to some extent the rupture release dynamics should the pipeline fail.

Two impurities that might be possible in CO<sub>2</sub> pipelines merit mention given their unique dangers to pipelines and the public: water and H<sub>2</sub>S. CO<sub>2</sub> pipelines are usually made from carbon steel and require special maximum water quality specifications typically measured in the part per million, or its equivalent, that prevents the possibility of free water forming anywhere in the pipeline system. The presence of free water in a CO<sub>2</sub> stream permits the formation of carbonic acid in the pipeline, an acid that has a ferocious appetite for carbon steel. Given the rapidity and unpredictability at which carbonic acid can attack pipelines, prudent CO<sub>2</sub> pipeline operators have voluntarily established maximum water quality limitations for their input streams. Given the risks associated with carbonic acid attack, PHMSA should not leave this critical factor to company discretion, but instead should adopt federal regulations that specify a maximum water quality limitation for CO<sub>2</sub> pipelines.

Hydrogen sulfide, or H<sub>2</sub>S, is mentioned here because of a curious item identified in an article related to a supercritical state CO<sub>2</sub> pipeline rupture failure in Mississippi in early 2020.<sup>25</sup> The observations noted in the article by responders of a “green cloud” from the pipeline release, is a possible indication of high levels of H<sub>2</sub>S. Further investigation indicates that the source of the CO<sub>2</sub> (Jackson Dome) has levels of H<sub>2</sub>S at 5 percent, or 50,000 ppm. In contrast, the Centers for Disease Control and Prevention states that a level of 300 parts per million is “immediately dangerous to life or health.”<sup>26</sup> While the H<sub>2</sub>S level that transitions into “sour” gas is not defined in federal

---

<sup>24</sup> For example, see Suoton P. Peletire, Nejat Rahmanian, Iqbal M. Mujtaba, “Effects of Impurities on CO<sub>2</sub> Pipeline Performance, Chemical Engineering Transactions,” Vol. 57, 2017.

<sup>25</sup> Dan Zegart Huffpost article, “The Gassing of Satartia,” August 26, 2021 at [https://www.huffpost.com/entry/gassing-satartia-mississippi-co2-pipeline\\_n\\_60ddea9fe4b0ddef8b0ddc8f](https://www.huffpost.com/entry/gassing-satartia-mississippi-co2-pipeline_n_60ddea9fe4b0ddef8b0ddc8f),

<sup>26</sup> <https://www.cdc.gov/niosh/idlh/7783064.html>. It is my understanding that while a few states have attempted to impose H<sub>2</sub>S limits on intrastate pipelines, there is no such federal pipeline safety regulation limiting H<sub>2</sub>S on transmission pipelines, even though there are OSHA H<sub>2</sub>S limits on workplace workers, much lower than 300 ppm.

pipeline safety regulations, serious questions need to be raised about this specific CO<sub>2</sub> pipeline operation.

For CCS generated CO<sub>2</sub> from fuel combustion emission, an expected source for CCS, H<sub>2</sub>S is not a likely contaminant of the stream with trace levels of H<sub>2</sub>S in the less than 1 ppm to be expected. Treatment for the removal of water and water quality enforcement control limitations, however, are critical for CCS pipelines transporting CO<sub>2</sub> from combustion sources. Yet, current federal pipeline safety regulations also do not require that this risk be addressed.

## **VI. Areas needing additional federal pipeline safety focus for CO<sub>2</sub> pipelines**

Based on my experiences, the following are my preliminary observations on specific areas where CO<sub>2</sub> pipeline safety regulation improvement efforts should focus.

- 1. PHMSA should update the definition of carbon dioxide in current regulation.**  
The current “carbon dioxide” definition incorporated into pipeline safety regulation is driven by EOR and does not or may not apply to all CO<sub>2</sub> pipelines that may be developed for CCS projects. Federal regulations need to be modified to assure that federal standards apply to all CO<sub>2</sub> transmission pipelines that transport CO<sub>2</sub> for CCS projects, including all supercritical, gas, and liquid CO<sub>2</sub> transmission pipelines.
- 2. PHMSA needs to identify in regulation the potential impact areas for CO<sub>2</sub> pipeline ruptures.**  
The unique, and potentially very large impact areas for CO<sub>2</sub> pipeline ruptures need to be developed, defined, and promulgated into pipeline regulations. As mentioned previously, these areas are most likely to be measured in miles, not feet.
- 3. Specific CO<sub>2</sub> pipeline federal regulations should not be based solely on industry Recommended Practices.**  
Changes in the CO<sub>2</sub> pipeline safety regulation are needed and should be prescribed to avoid misinterpretation or misuse. Recent efforts by many in the industry to rely on more performance-based standards, even those incorporated by reference, have proven ineffective and disastrous. Such industry efforts also remove an important party to pipeline safety regulatory development, the public. Ironically, it is the public that has the most to lose from inadequate pipeline safety regulation if such referenced citations are not clear, relevant, effective, and cannot be enforced in assuring pipeline safety.
- 4. PHMSA should specifically identify how to incorporate fracture propagation protection on CO<sub>2</sub> transmission pipelines.**  
Given the differential propensity for CO<sub>2</sub> pipelines to propagate fractures along the pipeline upon rupture, regulations should specifically list pipeline design methods to arrest CO<sub>2</sub> fracture propagation.

**5. PHMSA should mandate the use of odorant injection into CO<sub>2</sub> transmission pipelines.**

Given the inability to detect or observe a CO<sub>2</sub> pipeline release, it is time to require the use of odorant injection in such pipelines, especially those pipelines that are not in unpopulated areas, to assist the public in identifying dangerous releases.

**6. PHMSA should require CO<sub>2</sub> pipeline operators to update their required procedural manuals related to coordination with local emergency response agencies for CO<sub>2</sub> pipeline ruptures.**

The major differences and uniqueness of CO<sub>2</sub> pipeline releases compared to hydrocarbon pipelines require that pipeline operators improve the sections of their federally mandated operation, maintenance, and emergencies procedural manuals for emergency response to CO<sub>2</sub> pipeline ruptures.<sup>27</sup> In particular, operators must be required to periodically and fully inform, train, and equip key local officials and emergency responders with regard to special response actions unique to CO<sub>2</sub> pipeline releases. Moreover, upon a rupture, pipeline operators must inform state and local emergency personnel so that they can quickly and adequately protect impacted citizens and themselves.

**7. PHMSA should establish regulations setting specific maximum contaminant impurities for CO<sub>2</sub> pipelines.**

Given the various sources and the unique risk associated with the introduction of water into a CO<sub>2</sub> pipeline, PHMSA should prescribe the maximum concentration of water allowed in them. This requirement goes well beyond a quality specification given the ability of water to rapidly cause CO<sub>2</sub> pipeline failures in unpredictable ways. Given the wide range of impurity sources for CO<sub>2</sub> streams for CCS, PHMSA should review a full range of limits for all common impurities and consider establishing maximum levels for all impurities that pose a safety risk in federal pipeline safety regulations.

**8. PHMSA should strengthen federal regulations for conversion of existing pipelines to CO<sub>2</sub> pipeline service.**

It is not clear whether the public interest is best served by CO<sub>2</sub> shipment in existing transmission pipelines converted to CO<sub>2</sub> service. Further, the general conditions of PHMSA's advisory bulletin are not adequate for conversion to CO<sub>2</sub> pipelines. PHMSA should fully investigate the risks of such conversions and issue regulations appropriate to the serious risks that could result from repurposing a pipeline for CO<sub>2</sub> service.

## **VII. Conclusions**

Current federal minimum pipeline safety regulations focus on higher concentration CO<sub>2</sub> pipelines transporting CO<sub>2</sub> in a supercritical state for use in oil production. Such

---

<sup>27</sup> 49CFR§195.402 and 49CFR§192.605 Procedural manual for operations, maintenance, and emergencies.



regulations are incomplete or in conflict with the intent of CCS, to reduce CO<sub>2</sub> content in the atmosphere to address global warming. Federal pipeline safety regulation concerning CO<sub>2</sub> pipelines need specific changes to address the likely expansion of CO<sub>2</sub> transmission pipeline mileage expected by CCS efforts enhanced by the Acts of 2018 and 2021.

Certain manufacturing processes, such as ethanol and some hydrogen reforming refinery units, produce CO<sub>2</sub> emission that are very pure CO<sub>2</sub>, with only trace amounts of contaminants, that are higher priority choices for CCS and associated pipelines, most likely new liquid transmission pipelines, especially under the immense tax credits associated with the Acts of 2018 and 2021. Current federal pipeline safety regulations, however, are not adequate to deal with the additional pipeline risks associated with the expected significant increase in associated CO<sub>2</sub> transmission pipelines under CCS.

The country is ill prepared for the increase of CO<sub>2</sub> pipeline mileage being driven by federal CCS policy. Federal pipeline safety regulations need to be quickly changed to rise to this new challenge, and to assure that the public has confidence in the federal pipeline safety regulations.<sup>28</sup>

*Richard B Kuprewicz*

Richard B. Kuprewicz  
President,  
Accufacts Inc.

---

<sup>28</sup> Disclosure: The author prepared this report for the Pipeline Safety Trust but retained full editorial control. The author received compensation from the Pipeline Safety Trust and the Bold Alliance for the preparation of this report.